NGST MISSION ARCHITECTURE IPT Activity Report for June-October 1997

Pierre Bely 9 October 1997

YARDSTICK DESIGN STATUS

End-to-end model

- Model for the yardstick mission is complete (but several improvements are planned)
- Two months spent on documentation and clean up

Optical design

- FSM-induced defocus problem identified by simulation
- optics being redesigned

Sunshield

- contamination from sunshield and propulsion was found to be negligible
- materials investigation for selection of films (structural, thermal, contamination)

• Thermal analysis

- Sunshield thermal trade analysis complete
 - new baseline defined (no V-groove and 6 layers)
 - effect of slews is negligible
- OTA thermal trade analysis in progress

• Sparse actuator mirror study


- effect of CTE variations
- feasibility of using actuators to shape mirrors to correct for radius of curvature errors and cte variations

YARDSTICK DESIGN STATUS (Ctd)

- Tolerances for segmented optics
- Alternate OTA subarchitectures
 - secondary mirror support
 - primary mirror and support
- ISIM internal study under way
- SPIE conference
 - 12 oral papers (NASA + industry)
 - 7 poster papers
- Monographs series

YARDSTICK DESIGN STATUS (Ctd)

OTA Optics Optical design Mirrors Tolerancing Straylight Alignment scheme WF control **Thermal** Structure/Mechanical General design SM support PM backup structure PM& SM Actuator FSM **Fine Guiding**



SSM		
	+Structure/Mechanical ACS +Sunshield +Thermal	
	Cryocooler Power Data handling Communication Propulsion	

OBS LEVEL	
Orbit	
+ Contamination	
+ Mission operations	
I&T plan	
Mass estimate	
Cost estimate	
Flight/Ground SW	

Legend: First column: preliminary look (1996); second column: current work

complete or almost complete

+ started and well under way

ISIM INTERNAL STUDY GOALS

Produce a detailed (Phase A like) study of ISIM to:

- Confirm technical feasibility and cost estimate of the reference design,
- Confirm compatibility with overall NGST concept (OTA, SSM, operations)
- Serve as a rock solid "yardstick" design against which alternate proposals can be compared to,
- Establish corresponding floor science capability
- Serve as fall back designs if more ambitious designs fail to materialize.

ISIM INTERNAL STUDY GUIDELINES

- Instrument suite to include cameras and spectrographs for core science (will include MIR camera and spectrograph but will a-priori exclude additional non core instruments such as a coronograph)
- 9 months effort (must be finished well before Phase A starts (Feb 1999)) with potential extension to 12 months
- Study will be pushed to a level of details sufficient to uncover all potential problems
- But emphasis should be on expanding the work already done, not in creating alternate and potentially better designs (in particular duplication of work done by industry should be avoided)
- Technical approaches must be aggressive but with guaranteed feasibility (example: advanced detectors vs DMD)

ISIM INTERNAL STUDY PI-TEAM AND ADVISORS

A Science Instrument IPT will be re-activated to serve as a non-official advisory group

PI-TEAM

Pierre Bely - STScI - Team Leader

John Mather - GSFC

Richard Burg - JHU

Pete Stockman - STScI

Matt Greenhouse - GSFC

Piero Madau - STScI

LOCAL ADVISORY GROUP:

Eric Smith - GSFC

Pete Shu - GSFC

Rodger Doxsey STScI

Chris Burrows STScI

John MacKenty STScI

Anuradha Koratkar - STScI

Antonella Nota - STScI

Massimo Stiavelli - STScI

EXTERNAL ADVISORY GROUP:

Rodger Thompson U of A

Judy Pipher - U of Rochester

William Forest - U of Rochester

Jacky Fisher - NRL

Dave Redding - JPL

ASWG (for periodic reviews)

NGST MONOGRAPHS

- NGST monographs are intended to
 - document the studies done by the government team
 - communicate findings to industry and astronomical community.
- First series will include:
 - No 1. The NGST yardstick mission (Bely et al)
 - No 2. The Design Reference Mission (Stiavelli, et al)
 - No 3. Considerations on aperture configuration (Bely, Burrows, Stockman))
 - No 4. Considerations on guiding (Bely, Burg)
 - No 5. A simple dynamics model for NGST (Bely, Burg, Mosier, Perrygo)
 - No 6. Straylight analysis (Bely, Mehalick, Petro)
 - No 7. Optical tolerances for a segmented system (Redding)
 - No 8. Cost modeling (Targove, Kahan)
 - No 9. Comparison of sunshield implementations (Rodger Farley, Perrygo)
 - No 10. Potential orbits for NGST (Llyod Purves, Scott Benson, Michael Mesarch)
 - No 11. Sky coverage issues (A. Koratkar, P. Stockman)

GOALS FOR NEXT QUARTERLY

End to End modeling

- Peer review for the end to end model
- Improve current model
 - guider block (include pixelization, cross talk, wf errors)
 - model primary mirror actuators (LaRC)
 - improve FSM block (MSFC)
- Perform specific studies
 - DM optimization
 - RWA specification
 - compare DM vs PM correction
 - study alternate wavefront sensing (interferometer)
 - study alternate guiding system (multiple stars, roll star)
 - study alternate ACS scheme (Feeps etc..)
- Simulate entire alignment procedure (synergy with DCATT)
- Establish optimized error budget (based on the end to end model results)

GOALS FOR NEXT QUARTERLY (Ctd)

Other architecture studies

- Study impact of drift orbit (DRM, sky coverage, communications)
- Study data handling
- Perform a detailed study of the ISIM
- Continue and finalize the theoretical actuator/thermal mirror study (thin shell)

Revisit the SSM design

Note: These goals are contingent on an adequate level of technical support by NASA centers.